L'ANTIC COLONIAL

Model: AUTHENTIC 1L PURE

Codes: 100171983 Group: G-265

Format: 24X220X1,35CM



ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 20% y 25%.

COMPOSITION							
	Size	Material	Type of material				
Layer 1	0.060-0.070	Oil	Natur Plus treatment				
Layer 2	3.5	Hardwood Layer	Oak wood				
Layer 3	10	Intermediate Layer	Softwood veneer				

LABORATORY TESTS						
Mass per surface	7.41 KG/M2	EN 14342*				
Thermal conductivity	0.133 W/M*K	UNE-EN 12667:2002*				
Heat resistance	0.09 M2*K/W	UNE-EN 12667:2002*				
Formaldehyde emissions	E1	EN 717*				
Gluing resistance	≥D3	DIN EN 204*				
Resistance to chair castors	No damage	DIN EN 425*				
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*				
Flammability	Dfl-s1	EN 13501*				
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*				
Slip resistance (pendulum-dry)	CL 3 (50)	UNE 41902*				
Slip resistance (dcof)	0.55	ANSI A137.1*				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023

AUTHENTIC 1L PURE

L'ANTIC COLONIAL

FEATURES



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Slight smoothing of the wood using a brush to achieve a surface with a slight relief



Applying a color oil or varnish on the wood surface in order to get different color ranges



Beveled cut on all 4 edges of the board for emphasizing size



Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.



Made with oak wood.



There are consistent color changes between pieces.

Material from a North American country.



Material from a European country.



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



3.5 mm

PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests $\,$



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.

PACKING					
Sales units per box	3.168 M2/BOX				
Sales units per pallet	104.544 M2/PAL				
Sales units per square meter	1 M2				
Sale unit	M2				
Base unit	ST				
Net weight	7.863636 KG/M2				
Gross weight	8.327652 KG/M2				

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100229370	IGUALACION AUTHENTIC PURE 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100176731	MAMPERLAN AUTHENTIC 1L PURE 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100229380	TRANSICION AUTHENTIC PURE 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100177641	ZOCALO AUTHENTIC PURE 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	2.58 KG/PIECES	2.6 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023 2/2