

Model: ELEGANT GREY PUL.L 120X120(A)

Codes: 100305811

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	8.5 MM	+/-5%*		
Width	1200 MM			
Length	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

^{*}ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11				
Breaking strength	2366 N	>1300N*		
Modulus of rupture	53 N/MM2	>=35N/mm2*		
Abrasion resistance	PEI 4 / 1500v			
Crazing resistance	Resists 3 cycles			

*ISO-13006:2018	UNE-EN	14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995				
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*		
Stain resistance	Class 5. Easy cleaning with water	3 Min.*		

*ISO-13006:2018	UNE-EN	14411:2016

Technical code-1 Use on medium traffic floors		SCOPE OF USE
	Technical code-1	Use on medium traffic floors

		ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028	
Slip resistance (pendulum-wet)	CLO		
*ISO 12006-2019 LINE EN 14411-2016			

PACKING				
Sales units per box	1.440092 M2/BOX			
Sales units per pallet	60.483871 M2/PAL			
Sales units per unit	1.440092 M2/PIECE			

System Certification





