## L'ANTIC COLONIAL

Model: JAVA 1L ASH Codes: 100270774 Group: G-257

Format: 9X54X1,4CM



	CC	OMPOSITION	
	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	APRESTO MATTE
Layer 2	3	Hardwood Layer	Oak wood
Layer 3	9	Intermediate Layer	Coniferous wood slats
Layer 4	2	Backside	Coniferous Wood

TOLERANCES		
Squareness of the item	0.2% of width.	

	LABORATORY TESTS	
Thermal conductivity	0.108 W/M*ºK W/M*K	UNE-EN 12667:2002**
Formaldehyde emissions	Clase E1	EN-717/1:2006**
Flammability	Dfl-S1	UNE EN 13501-1:2007**
Biological durability	Clase 2	
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*
Slip resistance (pendulum-dry)	CL 3 (65)	UNE 41902*
Slip resistance (dcof)	0.63	ANSI A137.1*





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023

JAVA 1L ASH

## L'ANTIC COLONIAL

## **FEATURES**



This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Is suitable for installing on water radiant heating



Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered



Made with oak wood.



Material from an Asian country.





Applying a color oil or varnish on the wood surface in order to get different color ranges.



Beveled cut on all 4 edges of the board for emphasizing size



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Format where only one board has been used to finish the entire base surface



It is necessary to apply adhesive for installing it.



There are considerable color changes between pieces.



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



It is necessary to apply adhesive for installing it.

	PACKING
Sales units per box	0.582996 M2/BOX
Sales units per pallet	51.303644 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	10.106417 KG/M2
Gross weight	10.518083 KG/M2





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023 2/2