Model: LEGEND 1L NEUTRAL Codes: 100110287 Group: G-263 Format: 26X220X1,5CM

## ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 15% y 20%. While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

COMPOSITION									
		Size	Material	Type of material					
	Layer 1	0.060-0.070	Oil	Natur treatment					
	Layer 2	4	Hardwood Layer	Oak wood					
	Layer 3	9	Intermediate Layer	Wood or HDF slats					
	Layer 4	2	Backside	Coniferous wood					

LABORATORY TESTS								
Mass per surface	>500 Kg/m2	EN 14342*						
Thermal conductivity	0.13 W/M*K	UNE-EN 12667:2002*						
Heat resistance	0.11 M2*K/W	UNE-EN 12667:2002*						
Formaldehyde emissions	E1	EN 717*						
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*						
Flammability	Dfl-s1	EN 13501*						
Bulk density	740 Kg/m3	UNE-EN 323:1994*						
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*						
Slip resistance (pendulum-wet)	CL 2 (38)	UNE 41901*						
Slip resistance (pendulum-dry)	CL 3 (60)	UNE 41902*						
Slip resistance (dcof)	0.54	ANSI A137.1*						



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

## 100110287 LEGEND 1L NEUTRAL

## L'ANTIC COLONIAL

	FEAT	URE:	S				
This installation system consists in assembling the b their edges by applying a slight pressure on the boa bonded with white glue. Tools are needed for the in	rds. The boards are then		The finish imitates traditional hand brushing of the wood, providing a rough and artisan look as the one cabinetmakers would achieve in the past.				
Applying a color oil or varnish on the wood surface in order to get different color ranges.			Combination of oils and waxes prepared for drying with UV lamps. With this finish, wood preserves the natural look of conventional oil but is more resistant to stains from everyday-use products and needs less maintenance. Advantages: Very natural look, low maintenance, and greater resistance to stains from water, wine, juice Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.				
30 Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.			Is suitable for installing on water radiant heating				
$\bigotimes$ Format where only one board has been used to finish the entire base surface			Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.				
It is necessary to apply adhesive for installing it.			Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.				
DAK Made with oak wood.			There are consistent color changes between pieces.				
Material from a European country.			Material from an Asian country.				
Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.			4 mm				
It is necessary to apply adhesive for installing it.			Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.				
	PAC	KING					
Sales units per box	3.432 M2/BOX						
Sales units per pallet	96.096 M2/PAL						
Sales units per square meter	1 M2						
Sale unit	M2						
Base unit	ST						
Net weight	8.477273 KG/M2						
Gross weight	8.980769 KG/M2						

SPECIAL PIECES											
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100114237	IGUALACION LEGEND NEUTRAL 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100176592	MAMPERLAN LEGEND 1L NEUTRAL 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES		
100114253	TRANSICION LEGEND NEUTRAL 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100114266	ZOCALO LEGEND NEUTRAL 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES		



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.