L'ANTIC COLONIAL

Model: MINI IMPERIAL 1L GREY

Codes: 100238188 Group: G-246

Format: 18X220X1,2CM



COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.05	Varnish	APRESTO MATTE			
	Layer 2	2.5	Hardwood Layer	Oak wood			
	Layer 3	8	Substrate	Wood or HDF slats			
	Layer 4	1.5	Backside				

LABORATORY TESTS							
Mass per surface	6.81 KG/M2	EN 13489*					
Thermal conductivity	0.117 W/M*K	UNE-EN 12667:2002*					
Heat resistance	0.102 M2*K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	≤0.05 ppm (E1)	EN 717-1*					
Gluing resistance	≥D3	EN 204*					
Resistance to chair castors	>25000 cycles	EN 425*					
Moisture content	5-9%	EN 13489*					
Flammability	Dfl-S1	EN 13501-1*					
Bulk density	740 Kg/m3	UNE-EN 323:1994*					
Biological durability	Clase 1						
Slip resistance (pendulum-wet)	CL 1 (35)	UNE 41901*					
Slip resistance (pendulum-dry)	CL 3 (60)	UNE 41902*					
Slip resistance (dcof)	0.63	ANSI A137.1*					





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023

MINI IMPERIAL 1L GREY

L'ANTIC COLONIAL

FEATURES



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief. $% \label{eq:controlled}$



Beveled cut on the long sides of the board in order to create a continuity effect



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.



Made with oak wood.



There are consistent color changes between pieces.



Material from a European country.



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



2.5 mm



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



It is necessary to apply adhesive for installing it.

	PACKING
Sales units per box	3.564 M2/BOX
Sales units per pallet	114.048 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	6.979798 KG/M2
Gross weight	7.40404 KG/M2

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100229467	IGUALACION MINI IMPERIAL 1L GREY 4,5X270	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100229489	MAMPERLAN MINI IMPERIAL 1L GREY 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100229521	TRANSICION MINI IMPERIAL 1L GREY 4X270	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100229478	ZOCALO MINI IMPERIAL 1L GREY 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	2.58 KG/PIECES	2.6 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

18/08/2023