Mass per surface

Thermal conductivity

Model: NATURE 1L GREY Codes: 100213783 Group: G-257 Format: 18X220X1,35CM

## L'ANTIC COLONIAL



## COMPOSITION

		Size	Material	Type of material
	Layer 1	0.060-0.070	Varnish	Apresto Mate treatment
	Layer 2	3.5	Hardwood Layer	Oak wood
	Layer 3	9	Intermediate Layer	FIR
	Layer 4	1	Backside	Coniferous wood

LABORATORY TESTS	
7.41 KG/M2	
0.122 W/M*K	UNE-EN 12667:2002*
0.110 M2*K/W	UNE-EN 12667:2002*

Heat resistance	0.110 M2*K/W	UNE-EN 12667:2002*
Formaldehyde emissions	≤0.05 ppm (E1)	DIN EN 717-1*
Gluing resistance	≥D3	DIN EN 204*
Resistance to chair castors	> 25000 ciclos	EN 425*
Moisture content	5-9%	EN 13489*
Flammability	Cfl-S1	EN 13501*
Bulk density	740 Kg/m3	UNE-EN 323:1994*
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*
Critical radiant flux	0.41 W/CM2 (Class II)	ASTM E648*
Slip resistance (pendulum-wet)	CL 3 (50)	UNE 41901*
Slip resistance (pendulum-dry)	CL 3 (60)	UNE 41902*
Slip resistance (dcof)	0.54	ANSI A137.1*



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

## 100213783 NATURE 1L GREY

## L'ANTIC COLONIAL

FEATURES							
Ð	It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly	٢	Slight smoothing of the wood using a brush to achieve a surface with a slight relief.				
$\langle \gamma \rangle$	Applying a color oil or varnish on the wood surface in order to get different color ranges.	$\bigcirc$	Beveled cut on the long sides of the board in order to create a continuity effect				
AM	L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.	30	Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.				
ð	Is suitable for installing on water radiant heating	$\bigcirc$	Format where only one board has been used to finish the entire base surface				
$\mathbf{O}$	Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.	Ś	It is necessary to apply adhesive for installing it.				
0	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.	ОАК	Made with oak wood.				
	There are consistent color changes between pieces.		Material from a European country.				
PEFC	PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests	۲	Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.				
3.5	3.5 mm	Ś	It is necessary to apply adhesive for installing it.				
0	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the plece.						
	PACKING						

	PACKING	
Sales units per box	3.168 M2/BOX	
Sales units per pallet	101.376 M2/PAL	
Sales units per square meter	1 M2	
Sale unit	M2	
Base unit	ST	
Net weight	7.868687 KG/M2	
Gross weight	8.34596 KG/M2	

SPECIAL PIECES										
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight	
100214394	IGUALACION NATURE GREY 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES	
100214379	MAMPERLAN NATURE 1L GREY 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES	
100214423	TRANSICION NATURE GREY 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES	
100214419	ZOCALO NATURE GREY 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES	



17/08/2023