

Model: TRECCIA BLANCO 59,6X150(A) Codes: 100314025 Water absorption: BIII - Revestimiento (10%<=E<=20%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	10.5 MM	+/-5%*		
Width	596 MM			
Length	1500 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2018 UNE-EN 14411:2016				

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Breaking strength	>1100	>600N*
Modulus of rupture	>23	>=12N/mm2*
Crazing resistance	Resists 3 cycles	
*ICO 12006-2019 LINE EN 14411-2016		

HYGIENIC FEATURES	
UNE-EN ISO 10545-13-14:1995	

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*
*ISO-13006:2018 UNE-EN 14411:2016		

SCOPE OF USE		
Technical code-1	Use on walls	
PACKING		
Sales units per box	2.681924 M2/BOX	
Sales units per pallet	53.638477 M2/PAL	
Sales units per unit	0.893975 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.