

Model: CALACATTA GREEN SILK 120X250 (6)(A)

Codes: 100272109

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length	2500 MM		
Thickness	6 MM		
Width	1200 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	

^{*}ISO-13006:2015 UNE-EN 14411:2017

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11
Breaking strenght	>1100 N
Modulus of rupture	>45 N/MM2
Abrasion resistance	<140

^{*}ISO-13006:2015 UNE-EN 14411:2017

		NIC FEATURES N ISO 10545-13-14
Chemical resistance	CLASE A	
Stain resistance	5	
*ISO-13006:2015 UNE-EN 14411:2017		

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1	
Slip resistance (pendulum-wet)	CLO	
Stain resistance	5	
4s	DRY>36-LOW_WET<25-HIGH	
Slip resistance (pendulum-dry)	>45	
*ISO-13006:2015 UNE-EN 14411:2017		

	SCOPE OF USE	
Technical code-1	Use on walls	
Technical code-2	Dry interior floors	

System Certification







100272109 CALACATTA GREEN SILK



	PACKING	
Sales units per box	3 M2/BOX	
Sales units per pallet	66 M2/PAL	
Sales units per unit	3 M2/PIECE	

System Certification





